




mastabond

masonry adhesive

mastabond is a plaster based cement for adhering plasterboard to masonry surfaces. It has a consistent working time of 30 to 50 minutes with a 60 - 80 minute setting time. It delivers a fast and secure bond allowing for quick and easy installation.

performance

Mixing

Mixes easily with electric mixer.

Body and Grab

Good body for easy placement of daubs and great initial grab.

Sustainable

Low VOC meeting sustainable building project requirements.

key benefits

- excellent grab
- easy to mix
- easy to apply



product information

product size	20kg paper bag
type	Setting powder cement
mixing ratio	1L of water to 2kg of mastabond
working time	30 – 50 minutes
setting time	60 – 80 minutes
system usage	✓Masonry walls ✗Jointing ✓Back-blocking ✗Cornice ✗Wet area systems ✗Fire rated systems
voc	<50g/L

application

- Use **mastabond** only for masonry adhesion applications.
- **mastabond** should not be used on walls over 3m high and walls that could get wet during service. It also cannot be used where the masonry substrate is more than 15mm out of plane.
- Walls must be dry and paint free, clean from oil, dust, efflorescence, release agents or any other material that could impair the bonding of **mastabond**.
- Always use clean tools and containers.
- Pour the required amount of clean tap water into a container. Add the powder into water, mixing continuously to a smooth consistency.
- Only mix enough cement to be used in 50 minutes and do not contaminate with previously mixed batches. Once the material starts to set it cannot be remixed.

optimise product performance by:

- Storing in a dry, well ventilated environment fully protected from the weather.
- Washing tools before product dries and hardens.
- Ensuring **mastabond** does not dry out before setting has taken place under severe hot dry conditions.



The following Siniat products have been independently certified by Global GreenTag to GreenRate Level A: **mastashield**, **fireshield**, **impactshield**, **soundshield**, **watershield**, **spanshield**, **multishield**, **curveshield**, **opal**, **trurock**, **trurock hd**, **shaftliner** and **intershield**. Compliance certificates are available on siniat.com.au.



Quality
ISO 9001




All Siniat products have been developed to meet the specific needs of the Australian market.

All Siniat Australian manufacturing sites comply with AS/NZ ISO 9001.



A wide range of plasterboard and metal products are available under the Opt2Act carbon neutral program. Opted-in products are certified carbon neutral by Climate Active. Visit www.siniat.com.au/opt2act to find out more.



Register for My Siniat!

My Siniat is an online technical hub where you can access everything you need for a compliant and successful project. It is your all-in-one digital platform for specifying, planning, and managing your Siniat wall and ceiling systems.

By registering for this platform, you will gain exclusive access to technical content, including System Selector, Project Proposal and the Siniat BIM and CAD Library.

You will also gain access to the **Siniat Academy** - a valuable training portal that provides a range of courses to learn more about our products and their applications. Courses are delivered in a fun and interactive way, and a certificate of completion is provided at the end of each module.

Register for My Siniat on siniat.com.au.

Disclaimer

Products manufactured and systems designed by Etex Australia Pty Ltd and branded Siniat, are produced in accordance with the Building Code of Australia and relevant Australian Standards. Information in this document is to be used as a guide only and is subject to project approval as many aspects of construction are not comprehensively covered. It is also the responsibility of the project to determine if Siniat's products and systems are suitable for the intended application. Etex Australia Pty Ltd will not be held responsible for any claims resulting from the installation of its products or other associated products not in accordance with the recommendations of the manufacturer's technical literature or relevant Australian Standards. Siniat technical information is regularly updated. To ensure this document is current with the latest information, visit siniat.com.au



Etex Australia Pty Ltd

ABN 61 003 621 010
31 Military Road, Matraville
NSW 2036

siniat.com.au



warranty

Siniat's products are guaranteed by a 10 Year Warranty. For details visit siniat.com.au

technical advice
AU 1300 724 505