



mastacoat3

jointing compound

mastacoat3 is an all purpose jointing compound suitable for bedding tape, second and final coating plasterboard joints.

mastacoat3 is premixed and ready to use. It is ideal in renovations and smaller jobs such as maintenance and prepaint repairs.

performance

Body

Exceptional body and ease of trowelling.

Drying

The perfect amount of time to obtain good thin edges when feathering as it does not dry out too fast.

Colour

A brown colour when applied making it easy to determine progress of jointing. The change in colour as **mastacoat3** dries ensures sanding is commenced only when the joints are completely dry. The dark colour is also useful for identifying patches for sanding, following minor repairs to walls at the completion of the job.

Sanding

Quick and very easy to sand.

Safe to Use

Low VOC meeting sustainable building project requirements.

key benefits

- premixed for easy use
- easy to clean
- minimal wastage



product information

product size	4kg bucket
type	Light weight air drying premixed all purpose compound.
drying time	Allow 24 hours. Drying time varies depending on temperature and humidity.
system usage	✓ Bedding ✓ Second coat ✓ Final coat ✓ Standard ✓ Y Fire rated
approximate density	1.2 g/cm ³

application

- **mastacoat3** is ready to use for hand trowelling.
- Test for consistency. If necessary add clean tap water in small amounts and mix until desired consistency is achieved.
- As with all compounds, excessive thinning may cause cracking or increased shrinkage. Do not mix with any other material.
- Maintain a minimum 10°C working temperature during application and drying.
- When using **mastacoat3** as an all purpose, ensure all joints are back-blocked.
- Allow sufficient drying time between coats and before sanding, depending on season/climate. We recommend 24 hours.
- Sand lightly by hand using 180 to 220 grit sand paper.
- A three coat paint system must be used in accordance with AS/NZS 2311 Guide to the painting of buildings. This consists of a sealer undercoat and two coats of paint.
- Both the quality of the paint and how it is applied have a large effect on the finished appearance of the plasterboard. The paint manufacturer's instructions for application must be followed. To achieve the best result it is strongly recommended that each coat of the three coat paint system be roller applied.

optimise product performance by:

- Firmly closing the lid to prevent the compound from drying out.
- Washing tools before product dries and hardens.
- Storing in a dry, well ventilated environment fully protected from the weather.



Quality
ISO 9001
SAI GLOBAL

All Siniat products have been developed to meet the specific needs of the Australian market. Products manufactured in Australia comply with quality systems certified as complying with AS/NZS ISO 9001:2008 and meet the requirements of AS/NZS 2588, Gypsum Plasterboard.



The following Siniat products have been independently certified by Global GreenTag to GreenRate Level A: **mastashield**, **fireshield**, **fireshield h**, **soundshield**, **watershield**, **spanshield**, **multishield**, **curveshield**, **opal**, **trurock** and **trurock HD**. Compliance certificates are available on siniat.com.au.



All Siniat plasterboard and metal products are available on the Siniat Carbon Neutral Opt-In program to help you meet your sustainability goals. Visit siniat.com.au to find out more.

Disclaimer

Products manufactured and systems designed by Etex Australia Pty Ltd and branded Siniat, are produced in accordance with the Building Code of Australia and relevant Australian Standards. Information in this document is to be used as a guide only and is subject to project approval as many aspects of construction are not comprehensively covered. It is also the responsibility of the project to determine if Siniat's products and systems are suitable for the intended application. Etex Australia Pty Ltd will not be held responsible for any claims resulting from the installation of its products or other associated products not in accordance with the recommendations of the manufacturer's technical literature or relevant Australian Standards. Siniat technical information is regularly updated. To ensure this document is current with the latest information, visit siniat.solutions

Siniat.solutions provides a host of online solutions for your product

siniat SELECT®

offers an online system selector and custom design specification proposal, developed by us and catered to your project's requirements.

siniat CALCULATE®

is a range of online calculation tools for the professional. Explore siniat.solutions on siniat.com.au.



Etex Australia Pty Ltd

ABN 61 003 621 010
31 Military Road, Matraville
NSW 2036

siniat.com.au



warranty

Siniat's products are guaranteed by a 10 Year Warranty. For details visit siniat.com.au

technical advice
AU 1300 724 505